

ZITTO TECHNICAL SHEET



Technical attributes

- Patented attraction mechanism with human scent pheromones and CO2
- Light attraction system
- Manage settings LCD display
- Full remotely programmable
- Day/Night management
- Seasonal programs
- CO2 charge and supply consumption check
- Control of outgoing dispensing flow
- Wind detection to stop over 40 knots
- Built for all weather conditions
- Power: AC 220V | Consumption: 150 watts
- Solenoid valve piloting (currently 220V) for CO2 supply
- Power supply suction fan diameter 300mm with motor 220/230V -34Watt-10Win 1300/1550 RPM



	Specification	Applications
SMALL	<ul style="list-style-type: none">• Range: up to 800 mq• Height: 1 meter• Weight: 28 kg	<ul style="list-style-type: none">• Households and similar sized locations• Private areas at condominiums• Patio/Balcony
MEDIUM	<ul style="list-style-type: none">• Range: up to 2000 mq• Height: 1,3 meters• Weight: 35 kg	<ul style="list-style-type: none">• Households and similar sized locations• Public and private areas at condominiums• HoReCa• Golf and yacht clubs• Enterprises
LARGE	<ul style="list-style-type: none">• Range: up to 4000 mq• Height: 1,5 meters• Weight: 42 kg	<ul style="list-style-type: none">• Smart Cityies• Municipalities• Hospitals• Schools• City parks